# This Page Is Inserted by IFW Operations and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

### IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

#### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims** Claims 1-5 (canceled) Claim 6. (currently amended) A hot gas filtration apparatus comprising: a vessel; a plurality of filter elements mounted within said vessel and positioned such that hot gas flows through said filter elements, each of said filter elements having a porous body. The hot gas filtration apparatus of claim 1, wherein the porous body includes an outer surface and an inner surface, said porous body forming a substantially closed figure having a closed end and an open end, said open end formed to be coupled to a support structure, said porous body defining a channel beginning at said open end and terminating at said closed end through which a filtered clean gas can flow into the clean gas side of a hot gas clean up system, said porous body defining a flange at said open end for attachment to said support structure: a first catalytic layer on surfaces within the porous body; and a porous membrane positioned on said outer surface of said porous body; and said membrane including a second catalytic layer. Claim 7 (canceled) Claim 8. (currently amended) The hot gas filtration apparatus of claim 76, further comprising: a porous membrane positioned on said inner surface of said porous body; and said membrane including a third catalytic layer. Claim 9. (original) The hot gas filtration apparatus of claim 8, wherein said second and third

a porous membrane positioned on said inner surface of said porous body; and

Claim 10 (original) The hot gas filtration apparatus of claim 6, further comprising:

said membrane including a second catalytic layer.

catalytic layers include different catalysts.

Claims 11 – 12 (canceled) .
Claim 13. (currently amended) A hot gas filtration apparatus comprising:
a vessel;
a plurality of filter elements mounted within said vessel and positioned such
that hot gas flows through said filter elements, each of said filter elements having a porous
body; and
a catalytic layer on surfaces within the porous body. The hot gas filtration
apparatus of claim 1, wherein the catalytic layer comprises:
a perovskite mixed catalyst of the composition ABO <sub>3</sub> ;
wherein A includes one of an alkali, alkaline earth, rare earth, and lanthanide
elements; and
wherein B includes an element from one of groups IB, IVB, VB, VIB, VIIB,
and VIII.
Claim 14. (original) The hot gas filtration apparatus of claim 13, wherein A includes one of
lanthanum, strontium, and a mixture of lanthanum and strontium; and
wherein B includes one of cobalt, nickel, copper, and manganese.
Claim 15. (currently amended) A hot gas filtration apparatus comprising:
a vessel;
a plurality of filter elements mounted within said vessel and positioned such
that hot gas flows through said filter elements, each of said filter elements having a porous
that hot gas flows through said filter elements, each of said filter elements having a porous body; and
body; and
a catalytic layer on surfaces within the porous body. The hot gas filtration
a catalytic layer on surfaces within the porous body. The hot gas filtration apparatus of claim 1, wherein the catalytic layer comprises:

Claim 16. (currently amended) A hot gas filtration apparatus comprising:
a vessel;
a plurality of filter elements mounted within said vessel and positioned such
that hot gas flows through said filter elements, each of said filter elements having a porous
body; and
a catalytic layer on surfaces within the porous body. The hot gas filtration
apparatus of claim 1, wherein the catalytic layer comprises:
a perovskite structure of the form $(A_1)_m(A_2)_n(B_1)_p$ $(B_2)_qO_3$ ;
wherein A <sub>1</sub> includes a rare earth element;
wherein A <sub>2</sub> includes one of Sr, Ba, and Pb;
wherein B <sub>1</sub> includes one of Ni, Co, Fe, Zn, Cu, and Mn; and
wherein B <sub>2</sub> includes one of Ru, Os, Ir, Pt, Ti, Mo. W, Nb, Mn, Ta, and Sb.
Claim 17. (currently amended) A hot gas filtration apparatus comprising:
a vessel;
a plurality of filter elements mounted within said vessel and positioned such
that hot gas flows through said filter elements, each of said filter elements having a porous
body; and
a catalytic layer on surfaces within the porous bodyThe hot gas filtration
apparatus of claim-1, wherein the catalytic layer comprises:
a zeolite of the form $(A)[(B) O_2)_n \times H_2O)$ ;
wherein A includes one of Na <sub>2</sub> , K <sub>2</sub> , Ca, and Ba; and
wherein B includes one of Al and Si.
Claim 18. (currently amended) A hot gas filtration apparatus comprising:
a vessel;
a plurality of filter elements mounted within said vessel and positioned such
that hot gas flows through said filter elements, each of said filter elements having a porous
body; and
a catalytic layer on surfaces within the porous bodyThe hot gas filtration
apparatus of claim 1, wherein the catalytic layer comprises a spinel of the form (A)(Al) Ox,
and wherein A includes one of Mg, Fe, Zn, and Mn.
Claim 19. (canceled)